# 28B0-D3-A00D00-00 | CMC28



### Empty CMC28 2000W HVAC Empty Outdoor Equipment Cabinet

The cabinet is designed to house rack mounted equipment. This includes DC power systems, Fiber storage/splice trays, cell site routers, batteries, and other rack mounted equipment. This cabinet provides mechanical and environmental protection for the equipment inside.

- Excellent Thermal Performance compatible with thermosiphon or HVAC
- Provides mounting space for power distribution, network servers, batteries, or other equipment.
- Front door compatible with Pad Lock.
- Provides flexible access for the cable entrances.
- Optional heater for cold environments.
- Provides 28RU of 19" or 23" Rack Space for Equipment
- Common parts available across the same platform.

#### Product Classification

Product Type Outdoor cabinet

Product Series CMC

## General Specifications

Access Front door | Removable panel

Alarm Type Door alarm | HVAC alarms (including high temperature, failure) | S2 module, 20P or

standard and user defined alarms

**Batteries** Not included

Batteries Supported 9

Capacity 1000 W Heater

**Color** Gray

Cooling 3000W HVAC | 380 W/k Thermosiphon

**Door Security**Quarter turn lock, puck lock system for rear door | Swing handle, puck lock system for front

door

Mounting H-frame | Pad | Pole | Universal wall mount

Noise Emission, maximum 65 dBA

Rack Type EIA 19 in | EIA 23 in



## 28B0-D3-A00D00-00 | CMC28

Rack Units 28

**Dimensions** 

 Height
 1,447.8 mm | 57 in

 Width
 711.2 mm | 28 in

 Depth
 711.2 mm | 28 in

**Electrical Specifications** 

**Battery String Current, maximum** 170 A-h @ -48 Vdc

Battery Strings, quantity 3 @ -48 Vdc

Cooling Capacity 3800 W

**dc Distribution Type** 19" or 23" Rack DC Distribution Panels or DIN Breakers

Voltage -48 Vdc

Material Specifications

Finish Powder coated | UV resistant

Material Type Aluminum

**Environmental Specifications** 

Operating Temperature  $-40 \,^{\circ}\text{C} \text{ to } +46 \,^{\circ}\text{C} \text{ (-40 °F to } +115 \,^{\circ}\text{F)}$ 

Storage Temperature  $-40 \, ^{\circ}\text{C} \text{ to } +70 \, ^{\circ}\text{C} \left(-40 \, ^{\circ}\text{F to } +158 \, ^{\circ}\text{F}\right)$ 

Environmental Space UV resistant for outdoor

**Qualification Standards** IP55 | Telcordia GR-487

**Thermal Compliance** GR-487

Packaging and Weights

**Weight, net** 95.254 kg | 210 lb

Regulatory Compliance/Certifications

Agency Classification

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

