FJ-02VAADDC

HELIAX® Discrete MULTIMODE FIBER JUMPER Cca ARMOR AOPC SHROUD.

Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Product Type	Wireless Fiber Cable Assemblies
Product Brand	HELIAX®
Product Series	FJ
Ordering Note	ANDREW® non-standard product
General Specifications	
Color, connector A	Aqua
Color, connector B	Aqua
Construction Type	Discrete fiber tail
Interface, Connector A	LC
Interface Feature, connector A	Standard
Interface Body Style, connector A	Straight
Interface, Connector B	LC
Interface Feature, connector B	Outdoor
Interface Body Style, connector B	Straight
Jacket Color	Black
Total Fibers, quantity	2
Dimensions	
Cable Assembly Length Range (m)	3 - 5
Diameter Over Jacket	5 mm 0.197 in
Optical Specifications	
Fiber Mode	Multimode
Fiber Type	OM4, bend insensitive
Insertion Loss, typical note	Insertion loss is measured at 1310 and 1550 nm



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: May 16, 2025

FJ-02VAADDC

Insertion Loss, typical	0.5 dB	
Environmental Specifications		
Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)	
Environmental Space	Outdoor	
Packaging and Weights		
Cable weight	35 kg/km 23.519 lb/kft	
* Footpotor		

* Footnotes

Insertion Loss, typical note Insertion loss is measured at a room temp of +20°C (+68°F)

an Amphenol company

©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: May 16, 2025