

LS2-HMPHMP-8M-W-D



D-CLASS LSF2-50 SureFlex® Jumper with interface types 4.3-10 Push-Pull Male and 4.3-10 Push-Pull Male with HELIAX® SureGuard weatherproofing, 8M

- WARNING: DO NOT MATE WITH 4.1-9.5 DIN

Product Classification

Product Type	SureFlex® D-CLASS, dynamic PIM
Product Brand	HELIAX® SureFlex®
Product Series	LSF2-50

General Specifications

Body Style, Connector A	Push-pull
Body Style, Connector B	Push-pull
Interface, Connector A	4.3-10 Male
Interface, Connector B	4.3-10 Male

Dimensions

Length	8 m 26.247 ft
Nominal Size	3/8 in

Logo Image

LS2-HMPHMP-8M-W-D



Electrical Specifications

3rd Order IMD Dynamic	-119 dBm
3rd Order IMD Dynamic Test Method	Two +43 dBm carriers per IEC 62037

VSWR/Return Loss

Frequency Band	VSWR	Return Loss (dB)
698-970 MHz	1.106	26
1700-2200 MHz	1.106	26
2200-2700 MHz	1.106	26
3400-3800 MHz	1.222	20
4000-6000 MHz	1.288	18

Jumper Assembly Sample Label

LS2-HMPHMP-8M-W-D



Environmental Specifications

Weatherproofing Method HELIAX® SureGuard weatherproofing boot