


# RRZZVV-65B-R8NV3D



12-port sector antenna, 4x 694–960, 4x 1427–2690 and 4x 1695–2690 MHz, 65° HPBW, 8x RET

- SEED® antenna providing high gain and improved efficiency
- High radiation and pattern efficiency for improved coverage area, capacity or reduced power consumption for a given area
- Reduces the amount of aluminum used to minimize CO2 release
- Innovative aerodynamic shape optimized for reduced wind loading in every direction
- Retractable tilt indicator rods
- Independent Tilt DIPLEXED Antenna for 1800/2100 and for 2600 MHz when used with 4T4R multi-band radios

## General Specifications

<b>Antenna Type</b>	Sector
<b>Band</b>	Multiband
<b>Color</b>	Light Gray (RAL 7035)
<b>Grounding Type</b>	RF connector inner conductor and body grounded to reflector and mounting bracket
<b>Performance Note</b>	Outdoor usage
<b>Radome Material</b>	Fiberglass, UV resistant
<b>Reflector Material</b>	Aluminum
<b>RF Connector Interface</b>	4.3-10 Female
<b>RF Connector Location</b>	Bottom
<b>RF Connector Quantity, mid band</b>	8
<b>RF Connector Quantity, low band</b>	4
<b>RF Connector Quantity, total</b>	12

## Remote Electrical Tilt (RET) Information

<b>RET Hardware</b>	CommRET v2
<b>RET Interface</b>	8-pin DIN Female   8-pin DIN Male
<b>RET Interface, quantity</b>	2 female   2 male
<b>Input Voltage</b>	10–30 Vdc
<b>Internal RET</b>	Low band (2)   Mid band (6)
<b>Power Consumption, active state, maximum</b>	8 W
<b>Power Consumption, idle state, maximum</b>	1 W


# RRZZVV-65B-R8NV3D

**Protocol** 3GPP/AISG 2.0 (Single RET)

## Dimensions

**Width** 430 mm | 16.929 in  
**Depth** 197 mm | 7.756 in  
**Length** 2100 mm | 82.677 in  
**Net Weight, antenna only** 39.6 kg | 87.303 lb


## Array Layout



Array ID	Frequency (MHz)	RF Connector	HPBW	RET (SRET)	AISG No.	AISG RET UID
B1	694-960	1 - 2	65°	1	AISG1	CPxxxxxxxxxxxxxxxxR1
B2	694-960	3 - 4	65°	2	AISG1	CPxxxxxxxxxxxxxxxxR2
B1	1695-2180	5 - 6	65°	3	AISG1	CPxxxxxxxxxxxxxxxxB1
B2	1695-2180	11 - 12	65°	4	AISG1	CPxxxxxxxxxxxxxxxxB2
Y1	2490-2690	7 - 8	65°	5	AISG1	CPxxxxxxxxxxxxxxxxY1
Y2	1427-2690	9 - 10	65°	6	AISG1	CPxxxxxxxxxxxxxxxxY2
Y3	1427-2690	11 - 12	65°	7	AISG1	CPxxxxxxxxxxxxxxxxY3
Y4	2490-2690	13 - 14	65°	8	AISG1	CPxxxxxxxxxxxxxxxxY4


(Color of colored boxes are not true depictions of array sizes)

## Port Configuration



## Logo Image

# RRZZVV-65B-R8NV3D



## Electrical Specifications

<b>Impedance</b>	50 ohm
<b>Operating Frequency Band</b>	1427 – 2690 MHz   1695 – 2690 MHz   694 – 960 MHz
<b>Polarization</b>	±45°
<b>Total Input Power, maximum</b>	1,200 W @ 50 °C

## Electrical Specifications

	<b>R1,R2</b>	<b>R1,R2</b>	<b>R1,R2</b>	<b>B1,B2</b>	<b>B1,B2</b>	<b>Y1,Y4</b>
<b>Frequency Band, MHz</b>	<b>698–806</b>	<b>790–894</b>	<b>890–960</b>	<b>1695–1995</b>	<b>1920–2180</b>	<b>2490–2690</b>
<b>RF Port</b>	1,2,3,4	1,2,3,4	1,2,3,4	5,6,11,12	5,6,11,12	5,6,11,12
<b>Gain at Mid Tilt, dBi</b>	14.6	15.4	15.8	17.4	18	18.5
<b>Beamwidth, Horizontal, degrees</b>	73	63	58	70	67	64
<b>Beamwidth, Vertical, degrees</b>	10.4	9.5	8.8	5.5	5	4
<b>Beam Tilt, degrees</b>	2–12	2–12	2–12	2–12	2–12	2–12
<b>USLS (First Lobe), dB</b>	16	17	17	15	16	20
<b>Front-to-Back Ratio at 180°, dB</b>	28	28	29	30	29	28
<b>Front-to-Back Total Power at 180° ± 30°, dB</b>	20	22	22	25	23	23
<b>Isolation, Cross Polarization, dB</b>	25	25	25	26	26	26
<b>Isolation, Inter-band, dB</b>	25	25	25	26	26	26
<b>VSWR   Return loss, dB</b>	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0
<b>PIM, 3rd Order, 2 x 20 W, dBc</b>	-153	-153	-153	-153	-153	-153
<b>Input Power per Port at 50°C, maximum, watts</b>	300	300	300	180	180	180

# RRZZVV-65B-R8NV3D

## Electrical Specifications

	Y2,Y3	Y2,Y3	Y2,Y3	Y2,Y3	Y2,Y3
<b>Frequency Band, MHz</b>	<b>1427–1518</b>	<b>1695–1995</b>	<b>1920–2300</b>	<b>2300–2500</b>	<b>2490–2690</b>
<b>RF Port</b>	7,8,9,10	7,8,9,10	7,8,9,10	7,8,9,10	7,8,9,10
<b>Gain at Mid Tilt, dBi</b>	15.6	17.7	18.4	19.5	19.9
<b>Beamwidth, Horizontal, degrees</b>	79	64	61	57	54
<b>Beamwidth, Vertical, degrees</b>	7.5	5.8	5.2	4.5	4.1
<b>Beam Tilt, degrees</b>	2–12	2–12	2–12	2–12	2–12
<b>USLS (First Lobe), dB</b>	14	18	18	16	17
<b>Front-to-Back Ratio at 180°, dB</b>	33	33	34	35	37
<b>Front-to-Back Total Power at 180° ± 30°, dB</b>	24	26	27	28	31
<b>Isolation, Cross Polarization, dB</b>	25	26	26	26	26
<b>Isolation, Inter-band, dB</b>	25	26	26	26	26
<b>VSWR   Return loss, dB</b>	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0
<b>PIM, 3rd Order, 2 x 20 W, dBc</b>	-153	-153	-153	-153	-153
<b>Input Power per Port at 50°C, maximum, watts</b>	250	250	250	200	200

## Mechanical Specifications

<b>BASTA Version, mechanical</b>	BASTA v12
<b>Wind Loading @ Velocity, frontal</b>	494.0 N @ 150 km/h (111.1 lbf @ 150 km/h)
<b>Wind Loading @ Velocity, lateral</b>	266.0 N @ 150 km/h (59.8 lbf @ 150 km/h)
<b>Wind Loading @ Velocity, maximum</b>	780.0 N @ 150 km/h (175.4 lbf @ 150 km/h)
<b>Wind Loading @ Velocity, rear</b>	319.0 N @ 150 km/h (71.7 lbf @ 150 km/h)
<b>Wind Speed, maximum</b>	241 km/h (150 mph)

## Packaging and Weights

<b>Width, packed</b>	530 mm   20.866 in
<b>Depth, packed</b>	349 mm   13.74 in
<b>Length, packed</b>	2272 mm   89.449 in
<b>Weight, gross</b>	49.4 kg   108.908 lb

# RRZZVV-65B-R8NV3D

---

## Regulatory Compliance/Certifications

<b>Agency</b>	<b>Classification</b>
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
UK-ROHS	Compliant


## Included Products

BSAMNT-2F	-	Mounting bracket for cylindrical pipe installations (60-115mm pipe diameter) for fix mechanical tilt applications.
-----------	---	--

## \* Footnotes

<b>Performance Note</b>	Severe environmental conditions may degrade optimum performance
-------------------------	---

# BSAMNT-2F



Mounting bracket for cylindrical pipe installations (60-115mm pipe diameter) for fix mechanical tilt applications.

## Product Classification

**Product Type** Fixed tilt mounting kit

## General Specifications

**Application** Outdoor

**Color** Silver

## Dimensions

**Compatible Diameter, maximum** 115 mm | 4.528 in

**Compatible Diameter, minimum** 60 mm | 2.362 in

**Weight, net** 3.8 kg | 8.378 lb

## Material Specifications

**Material Type** Galvanized steel

## Packaging and Weights

**Included** Brackets | Hardware

**Packaging quantity** 1

**Weight, gross** 4 kg | 8.818 lb

## Regulatory Compliance/Certifications

Agency	Classification
CE	Compliant with the relevant CE product directives
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant
UK-ROHS	Compliant

# BSAMNT-2F

---

