F4A-PDMDR-12M

HELIAX® 1/2" SureFlex® Jumper with interface types 7-16 DIN Male and 7-16 DIN Male Right Angle, 12 m

Product Classification

Product Type	SureFlex® standard	
Product Brand	HELIAX® SureFlex®	
Product Series	RSJ4-50	
General Specifications		
Body Style, Connector A	Straight	
Body Style, Connector B	Right angle	
Interface, Connector A	7-16 DIN Male	
Interface, Connector B	7-16 DIN Male	
Specification Sheet Revision Level	А	
Dimensions		
Length	12 m 39.37 ft	
Nominal Size	1/2 in	
Electrical Specifications		
DTF, Connector A	-32 dB	
DTF, Connector B	-32 dB	
VSWR/Return Loss		

Frequency Band	VSWR, typical	Return Loss, typical (dB)
0-3000 MHz	1.106	25.96
2.2–2.7 GHz	1.083	27.99

Jumper Assembly Sample Label

Page 1 of 2



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

F4A-PDMDR-12M



Environmental Specifications

Immersion Test Method

Meets IEC 60529:2001, IP68 in mated condition

Regulatory Compliance/Certifications

Agency

ISO 9001:2015

Classification

Designed, manufactured and/or distributed under this quality management system



Page 2 of 2

©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025