F4A-PDMDM-12M

FSJ4-50B SureFlex® Jumper with interface types 7-16 DIN Male and 7-

Product Classification

Frequency Band	VSWR typical	Poturn Los	
VSWR/Return Loss			
DTF, Connector B	-32 dB		
DTF, Connector A	-32 dB		
Electrical Specifications			
Nominal Size	1/2 in		
Length	12 m 39.37 ft		
Dimensions			
Specification Sheet Revision Level	A		
Interface, Connector B	7-16 DIN Male		
Interface, Connector A	7-16 DIN Male		
Body Style, Connector B	Straight		
Body Style, Connector A	Straight		
General Specifications			
Product Series	FSJ4-50B		
Product Brand	HELIAX® SureFlex	(B	
Product Type	SureFlex® standard	SureFlex® standard	

Frequency Band	VSWR, typical	Return Loss, typical (dB)
0-3000 MHz	1.106	25.96
2.2–2.7 GHz	1.083	27.99

Jumper Assembly Sample Label

Page 1 of 2



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

F4A-PDMDM-12M



Environmental Specifications

Immersion Test Method

Meets IEC 60529:2001, IP68 in mated condition

Regulatory Compliance/Certifications

Agency

ISO 9001:2015

Classification

Designed, manufactured and/or distributed under this quality management system



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

Page 2 of 2