## F2A-NMNM-6-P

FSJ2P-50-100 SureFlex® Jumper with interface types N Male and N Male, 6 feet

Return Loss (dB)

### Product Classification

Product Type	SureFlex® Premium, static PIM
Product Brand	HELIAX®   SureFlex®
Product Series	FSJ2-50
General Specifications	
Body Style, Connector A	Straight
Body Style, Connector B	Straight
Interface, Connector A	N Male
Interface, Connector B	N Male
Specification Sheet Revision Level	А
Dimensions	
Length	1.829 m   6.001 ft
Nominal Size	3/8 in
Electrical Specifications	
3rd Order IMD Static	-110 dBm
3rd Order IMD Static Test Method	Two +43 dBm carriers
VSWR/Return Loss	

# VOVE/RELUTELOSS Frequency Band VSWR 698–960 MHz 1.101

698–960 MHz	1.101	26.36
1700–2200 MHz	1.101	26.36
2200-2700 MHz	1.101	26.36

### Jumper Assembly Sample Label

Page 1 of 2



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

## F2A-NMNM-6-P



### **Environmental Specifications**

**Immersion Test Method** 

Meets IEC 60529:2001, IP68 in mated condition

### Regulatory Compliance/Certifications

#### Agency

ISO 9001:2015

### Classification

Designed, manufactured and/or distributed under this quality management system



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

Page 2 of 2