F2A-NMNM-M5-P

FSJ2P-50-100 SureFlex® Jumper with interface types N Male and N
Male, 0.5M

Product Classification

Product Type SureFlex® Premium, static PIM

Product Brand HELIAX® | SureFlex®

Product Series FSJ2-50

General Specifications

Body Style, Connector AStraightBody Style, Connector BStraightInterface, Connector AN MaleInterface, Connector BN Male

Specification Sheet Revision Level A

Dimensions

Length 0.5 m | 1.64 ft

Nominal Size 3/8 in

Electrical Specifications

3rd Order IMD Static -110 dBm

3rd Order IMD Static Test Method Two +43 dBm carriers

VSWR/Return Loss

Frequency Band	VSWR	Return Loss (dB)
698-960 MHz	1.101	26.36
1700-2200 MHz	1.101	26.36
2200-2700 MHz	1.101	26.36

Jumper Assembly Sample Label





Environmental Specifications

Immersion Test Method

Meets IEC 60529:2001, IP68 in mated condition

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.andrew.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant

