# F1R-NMNM-5M-P

FSJ1RK-50B SureFlex® Jumper with interface types N Male and N Male,



**■** 5 m

#### **Product Classification**

**Product Type** SureFlex® Premium, static PIM

**Product Brand** HELIAX® | SureFlex®

**Product Series** FSJ1-50B

General Specifications

**Body Style, Connector A** Straight Straight **Body Style, Connector B** N Male Interface, Connector A N Male Interface, Connector B Α

**Specification Sheet Revision Level** 

**Dimensions** 

Length 5 m | 16.404 ft

**Nominal Size** 1/4 in

**Electrical Specifications** 

**3rd Order IMD Static** -107 dBm

3rd Order IMD Static Test Method Two +43 dBm carriers

### VSWR/Return Loss

Frequency Band	VSWR	Return Loss (dB)
698-960 MHz	1.15	23.13
1700-2200 MHz	1.15	23.13
2200-2700 MHz	1.15	23.13

Jumper Assembly Sample Label





## **Environmental Specifications**

EN50575 CPR Cable EuroClass Fire PerformanceB2caEN50575 CPR Cable EuroClass Smoke Rating\$1aEN50575 CPR Cable EuroClass Droplets Ratingd0EN50575 CPR Cable EuroClass Acidity Ratinga1

**Immersion Test Method**Meets IEC 60529:2001, IP68 in mated condition

## Regulatory Compliance/Certifications

Agency Classification

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

