# ATCB-DB15-010



RET control cable 10m with male DB15 and female AISG connector

- Feeds data and power to RET system components
- Directly connects RET actuator with RRH (Remote Radio Heads) with DB15 connector

#### OBSOLETE

This product was discontinued on: March 30, 2023

### Product Classification

Product Type	AISG DB15 cable
General Specifications	
AISG Connector A	8-pin DIN Female
AISG Connector A Body Style	Straight
AISG Connector A Standard	IEC 60130-9
Color	Black
Connector B	15-pin D-Sub Male
Data Conductor Type	0.24 mm² (24 AWG) twisted pair
EU Certification	CB   CE
Power Conductor Type	0.75 mm² (18 AWG) stranded
Dimensions	
Length	10 m   32.808 ft
Diameter Over Jacket	8 mm   0.315 in
Electrical Specifications	
Protocol	AISG 1.1   AISG 2.0
Voltage, maximum	300 V

### **Environmental Specifications**

Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Relative Humidity	Up to 100%

Page 1 of 2



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 12, 2025

# ATCB-DB15-010

Climatic Sequence Test Method	IEC 60068-2-14
Corrosion Test Method	IEC 60068-2-11, Test Condition Ka
Ingress Protection Test Method	IEC 60529:2001, IP67
UV Resistance Test Method	IEC 60068-2-5, Test Condition B

### Packaging and Weights

0.2 kg | 0.441 lb

## Regulatory Compliance/Certifications

Agency

ISO 9001:2015

Weight, net

#### Classification

Designed, manufactured and/or distributed under this quality management system

Page 2 of 2



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 12, 2025