

AT-6-43-MF



6 dB Coaxial Attenuator DC–6000 4.3-10 M-F

Product Classification

| | |
|-----------------------|---|
| Regional Availability | Asia Australia/New Zealand EMEA Latin America North America |
| Product Type | Attenuator |

General Specifications

| | |
|-----------------------|---------------|
| Device Type | Attenuator |
| Application | Indoor |
| Color | Silver |
| Inner Contact Plating | Silver |
| Interface | 4.3-10 Male |
| Interface 2 | 4.3-10 Female |
| Outer Contact Plating | Trimetal |

Electrical Specifications

| | |
|--------------------------|--------------|
| Return Loss, minimum | 20.8 dB |
| Attenuation | 6 dB |
| Attenuation Tolerance | ±0.5 dB |
| Average Power, maximum | 2 W |
| Impedance | 50 ohm |
| Operating Frequency Band | 0 – 6000 MHz |
| Peak Power, maximum | 0.5 kW |
| VSWR | 1.2 |

Environmental Specifications

| | |
|-----------------------|--------------------------------------|
| Operating Temperature | -40 °C to +85 °C (-40 °F to +185 °F) |
|-----------------------|--------------------------------------|

Regulatory Compliance/Certifications

AT-6-43-MF

| Agency | Classification |
|------------|-----------------------------------|
| CHINA-ROHS | Above maximum concentration value |
| ROHS | Compliant/Exempted |
| UK-ROHS | Compliant/Exempted |

