252130



Angle Adapter, universal, 3/8 in tapped hole (insert included)

Product Classification

Product Type Angle adapter

Product Brand I-Line

Ordering Note ANDREW® non-standard product

General Specifications

Adapter Type Angle adapter

Mounting 3/8 in tapped hole

Dimensions

Inside Width 16.002 mm | 0.63 in

Outside Width 38.1 mm | 1.5 in

Inside Length 16.002 mm | 0.63 in

Outside Length 46.99 mm | 1.85 in

Material Thickness 2.972 mm | 0.117 in

Material Specifications

Material Type Stainless steel

Mechanical Specifications

Installation Torque, maximum 13 ft lb | 17.626 N-m

Installation Torque, minimum 11 ft lb | 14.914 N-m

Maximum Loading Double stack, 1-5/8 in cable

Packaging and Weights

 Height, packed
 23.2 cm | 9.134 in

 Width, packed
 13.3 cm | 5.236 in

 Length, packed
 10.5 cm | 4.134 in



Page 1 of 4

25213C

Packaging quantity 10

Weight, gross 0.11 kg | 0.243 lb

Regulatory Compliance/Certifications

Agency Classification

REACH-SVHC Compliant as per SVHC revision on www.andrew.com/ProductCompliance

ROHS Compliant UK-ROHS Compliant

Included Products

UAAI – Universal Angle Adapter Insert



UAAI



Universal Angle Adapter Insert

Product Classification

Product Type Insert
Product Brand HELIAX®

Ordering Note ANDREW® non-standard product

General Specifications

Adapter Type Adapter

Mounting 3/8 in tapped hole

Dimensions

Outside Width12.7 mm | 0.5 inOutside Length25.4 mm | 1 inMaterial Thickness12.7 mm | 0.5 in

Material Specifications

Material Type Stainless steel

Mechanical Specifications

Maximum Loading Triple stack, 1-5/8 in cable

Packaging and Weights

 Height, packed
 4 cm | 1.575 in

 Width, packed
 5 cm | 1.969 in

 Length, packed
 1 cm | 0.394 in

Packaging quantity 10

Weight, gross 0.13 kg | 0.287 lb

Regulatory Compliance/Certifications



UAAI

Agency Classification

CHINA-ROHS Below maximum concentration value

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

REACH-SVHC Compliant as per SVHC revision on www.andrew.com/ProductCompliance

ROHS Compliant UK-ROHS Compliant

